



ErgonArmor
TECHNICAL COATING SOLUTIONS™



R-17-A-73 Asphalt Coating/Primer

SELECTION & SPECIFICATION DATA

Type	Oxidized Asphalt Cutback
Description	R-17-A-73 Asphalt Coating/Primer is a metal corrosion protection coating and asphalt primer packaged in a convenient aerosol spray can. It offers just the right amount of product for small jobs and touch up work.
Features	<ul style="list-style-type: none">• Packaged in convenient aerosol spray can• ANSI/NSF 61 certified• Penetrating and sealing primer• Quick drying (less than 5 minutes dry to touch)
Uses	<ul style="list-style-type: none">• Metal corrosion protection• Potable water service• Paving maintenance• Roofing primer• Ductile iron pipe and fittings (ID and OD)• Vehicle underbody
Color	Black
Finish	Gloss
Topcoats	Asphalt, acrylics, epoxies, polyurethanes. Consult ErgonArmor for more information.
Dry Film Thickness	1 – 2 mils per coat
Theoretical Coverage Rate	40 square feet per can at 2 coats

SUBSTRATES & SURFACE PREPARATION

All	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
-----	--

CLEANUP & SAFETY

Cleanup	Mineral spirits or equivalent solvent.
Safety	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
Ventilation	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

PACKAGING, HANDLING & STORAGE

Shelf Life	24 months at 75°F (24°C) when kept at recommended storage conditions and in original unopened containers.
Storage Temperature & Humidity	40°F – 110°F (4°C – 43°C) 0 – 100% relative humidity
Storage	Store indoors. Always inspect the product prior to use.
Package Sizes	12 cans per case (16 lbs per case) 1 pallet (100 cases per pallet)

Rev 12/18

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchase or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.



Division of Ergon Asphalt & Emulsions, Inc.

P.O. Box 1639, Jackson, MS 39215-1639 | 601-933-3381 Fax | 601-933-3595 Phone | 877-98ARMOR Toll-Free | ergonarmor.com